

TECHNICAL RIDER INFORMATION

O: 310.276.1158 F: 310.247.4896

CONSOLE-

DiGiCo SD 12 with BNC MADI D2 Snake 48 inputs, 16 analog and 8 digital outputs

MAIN PATCH-

40 ch. Snake to FOH / Located stage right

MAIN LOUDSPEAKERS CABINETS-

Main Fill

Six (6) L'Acoustics ARCS II 2-way active, constant curvature WST line source 22.5°x60° asymmetric directivity (LF 15" driver, HF 3" driver)

Balcony Fill

Four (4) L'Acoustics ARCS Focus 2-way passive, constant curvature WST line source 90°x15° directivity (LF 12" driver, HF 3" driver)

Center Fill

One (1) L'Acoustics 115XT HiQ coaxial active speaker 50° axi-symmetric directivity (LF 15" driver, HF 3" driver)

Side Fill

Two (2) L'Acoustics X12 passive 2-way coaxial enclosure. 90°x60° directivity (LF 12" driver, HF 3" driver)

Out Fill

One (1) L'Acoustics 12XTi coaxial passive speaker 90° axi-symmetric directivity (LF 12" driver, HF 3" driver)

SUBWOOFERS-

Four (4) L'Acoustics SB28 (2x18" Drivers each) One (1) 18" Rat Sub (L'Acoustics Processing)

ONSTAGE MONITOR WEDGES**-

Eight (8) EAW MW12, 2-Way, Full Range Coaxial Monitor 90° directivity (LF 12" driver, HF 3" driver)

Drum Wedge-

One (1) EAW- Eastern Acoustic Works MW15 2-Way, Full Range Coaxial Monitor, 15-inch woofer, 3-inch driver

One (1) Micro Sub 15 inch vented loaded Sub in Cone

**Nine (9) total wedge mixes

AMPLIFIERS-

FOH:

Two (2) L'Acoustics LA4X Two (2) L'Acoustics LA8

Monitors:

Five (5) Quattrocanali 4804 DSP+D

SIGNAL PROCESSING-

LA Network Manager FOH and SUBS Powersoft ArmoniaPlus

Waves SoundGrid Extreme Server V3r1 CPU: Intel® Core i7-10700

RAM: 8 GB

*(Engineer needs to provide computer and licenses)

All power feeding the sound system and stage gear is transformer isolated and isolated ground, ie., CLEAN POWER.

On Stage: 9x20 Amp 2 LED

POWER:

- 100 amps *single phase power
- 50ft of camlock gets you to stage right.
- Artist must provide camlock & distro

MICROPHONES-

1- AT Pro 35 • 1- Beta 87 2 - Blue 100i • 1 - Beta 91 3 - Beta 52 • 4 - Senn 935 4 - SM 57 • 10 - SM 58 3 - Beta 57 1 - EV RE 27 1 - D 112 • 6 - Senn 604 3 - Senn 609 • 6 - Senn 614 1 - Senn 904 2 - SM 94 • 2 - SM 81 2 - Senn 906

• 1 - KSM 9

OI Twelve (12) Passive Whirlwind

2 - AKG C414

CABLE: All Monster Cable Pro XLR (With Reinforced connections)

• 1- AUDIX D6

RECORDING:

- One (1) 40 Channel ISO Outs Of Main Patch
- 48 channels via DiGiCo UB MADI via USB \$150 fee to use own rig \$15 per channel to use house rig

STAGE LIGHTING SYSTEM-

Consoles:

Avolites Tiger Touch II

FIXTURES:

- Four (4) Robe Spiider
- Four (4) Robe Pointe
- Five (5) Robe T1 Profile
- Two (2) Robe Tetra 2
- Two (2) Chauvet Q Spot 560 LED
- Four (4) Chauvet Legend 412 LED
- Two (2) ETC Paletta 48
- Four (4) Chauvet Strike Array 4
- Four (4) ETC Source 4
- Twelve (12) Parcans

HAZER:

- Master FX
- Mystic- Premier Haze Generator

PROJECTOR:

- One (1) Epson EX9240
- 4,000 Lumen HD 1080P
- 3 LCD Technology
- Artist must provide playback device (laptop, DVD player, etc.) & suitable adapterse. Projector accepts VGA, S-Video, RCA and HDMI inputs.